

The major parts of Z-500 series pipe flowmeter: material of taper tube is polycarbonate(PC), the connectors are polyvinyl chloride(PA66), the float material is stainless steel or ABS, can be acidproof and alkali-resisting.

- Max. working pressure: 6Bar
- Temperature limit: 60°C
- Accuracy: $\pm 5\%$
- O-ring material: EPDM



Specifications

Model	Water		Pipe connection	Male Thread	Female Thread	Elbow (W)
	(GPM)	(LPM)				
Z-5008	0.1~1 0.2~2 0.5~5	0.5~4 1~7 1.8~18	ø20	1/2" BSP 1/2" NPT	/	1/2" NPT 1/2" BSP
Z-5008C	0.1~1 0.2~2 0.5~5	0.5~4 1~7 1.8~18	ø20	1/2" NPT 3/4" NPT	1/2" BSP	1/2" NPT 1/2" BSP
Z-5015	0.25~2.5 0.5-5 0.8-8	1~10 1.8~18 3~30	ø20	1/2" NPT 3/4" NPT	1/2" BSP	1/2" NPT 1/2" BSP
Z-5025	0.8-8 1-10	3-30 4-40	ø32	3/4" NPT	3/4" NPT 3/4" BSP	3/4" NPT 3/4" BSP
Z-5032	1.2~12 2-20 2.5-25	5-50 8-80 10-100	ø40	1" NPT	1" NPT 1" BSP	1" NPT 1" BSP
Z-5050	2.5-25 5-45 7-70	10-100 20-180 25-250	ø63	2" NPT	2" NPT 2" BSP	2" NPT 2" BSP
Z-5065	25~110 40-160 50~250	80-400 150-650 200-1000	ø75		2 1/2" NPT	/



Note: Other flow range is optional