


Z-400

Model	Measure Range		Thread (F/BSP)	Weight (Kg)	Working Pressure	Accuracy	Temperature (°C)
	GPM	LPM					
Z-4001	0.2~2	1~7	1/2"	0.2	≤6Bar	±6%	≤55
Z-4002	0.5~5	1.8~18	1/2"				
Z-4003	1~10	4~36	3/4"				
Z-4004	2~20	10~70	1"	0.65			
Z-4005	5~30	20~110	1"				
Z-4006	20~60	80~220	1½" Male				
Z-4007	30~110	100~400	2"	1.4			
Z-4008	50~150	180~600	2"				
Z-4009	60~200	200~800	2"				

Sizes(mm)

Model	Z-4001	Z-4002	Z-4003	Z-4004	Z-4005	Z-4006	Z-4007	Z-4008	Z-4009
A	210	210	278	265	265	306	345	345	345
B	32	32	45	51	51	51	75	75	75
C	Joint (PP) or 1Cr18Ni9Ti(304SS)								
D	O-ring(Silicon rubber or fluoro rubber)					O-ring(Nitrile rubber)			
E	Blocking ring (ABS)					101 (Nylon)			
F	Float 1Cr18Ni9Ti(304SS)								
G	Guide rod (316SS)								
H	Body(PMMA)								

